



# ORIENT

## Photo coupler

### Product Data Sheet

Part Number: OR-480

Customer: \_\_\_\_\_

Date: \_\_\_\_\_

#### 一级代理商：

深圳市弗瑞鑫电子有限公司

地址：深圳市宝安区西乡大道302号金源商务大厦B座三楼


0 -

0 - 0 0

.frxelec.

%"

- (1) Performance Specified for Common IPM Applications Over Industrial Temperature Range.
- (2) Short Maximum Propagation Delays
- (3) Minimized Pulse Width Distortion (PWD)
- (4) Very High Common Mode Rejection (CMR)
- (5) Hysteresis
- (6) Totem Pole Output (No Pull-up Resistor Required)
- (7) Available in Stretched SO-6 package.
- (8) Industrial temperature range: -40° C to 105° C
- (9) Safety approval
  - UL approved(No.E323844)
  - VDE approved(No.40029733)
  - CQC approved (No.CQC19001231480 )
- (10) In compliance with RoHS, REACH standard
- (11) MSL Level 1




&"

The OR-480 fast speed optocou- plers contain a GaAsP LED and photo detector with built-in Schmitt trigger to provide logic-compatible waveforms, eliminating the need for additional wave shaping. The totem pole output eliminates the need for a pull up resistor and allows for direct drive Intelligent Power Module or gate drive. Minimized propagation delay difference between devices make these optocou- plers excellent solutions for improving inverter efficiency through reduced switching dead time.

▪ "

- (1)IPM Interface Isolation
- (2)Isolated IGBT/MOSFET Gate Drive
- (3)AC and Brushless DC Motor Drives
- (4)Industrial Inverters
- (5)General Digital Isolation

("



V <sub>cc</sub>	V <sub>o</sub>
0	0
1	1
0	1
1	0

Note: A 0.1 μF bypass capacitor must be connected between pins 4 and 6



)"

Input	Average Forward Input Current	$I_F$	50	mA
	Peak transient input forward current	$I_{FPT}$	1	A
	Reverse Input Voltage	$V_R$	5	V
Output	Average Output Current	$I_O$	25	mA
	Supply Voltage	$V_{CC}$	25	V
	Output Voltage	$V_O$	25	V
	Output Collector Power Dissipation	$P_O$	210	mW
Insulation Voltage		$V_{iso}$	5000	Vrms
Working Temperature		$T_{opr}$	-40 + 100	°C
Storage Temperature		$T_{stg}$	-55 + 125	
*2 Soldering Temperature		$T_{sol}$	260	

\*1. Room temperature = 25 °C. Exceeding the maximum absolute rating can permanently damage the device. Working long hours at the maximum absolute rating can affect reliability.

\*2. soldering time is 10 seconds.

\*"

Power Supply Voltage	$V_{CC}$	4.5	20	V
Forward Input Current (ON)	$I_{F(ON)}$	6	10	mA
Forward Input Voltage (OFF)	$V_{F(OFF)}$	-	0.8	V
Operating Temperature	$T_A$	-40	100	°C



+

Logic Low Output Voltage	$V_{OL}$	—	0.08	0.5	V	$I_{OL} = 6.4 \text{ mA}$
Logic High Output Voltage	$V_{OH}$	2.4	4.9	—	V	$I_{OH} = -2.6 \text{ mA}$
		2.7	5			$I_{OH} = -0.4 \text{ mA}$
		2.7				$I_{OH} = -1.6 \text{ mA}$
Output Leakage Current ( $V_O = V_{CC} + 0.5V$ )	$I_{OHH}$	—	—	100	$\mu\text{A}$	$V_{CC} = 5 \text{ V}, I_F = 10\text{mA}$
		—	—	500	$\mu\text{A}$	$V_{CC} = 20 \text{ V}, I_F = 10\text{mA}$
High Level Supply Current	$I_{CCH}$	—	0.9	2.5	mA	$V_{CC} = 5.5 \text{ V}, I_F = 10 \text{ mA}, I_O = \text{Open}$
		—	1.1	2.5	mA	$V_{CC} = 20 \text{ V}, I_F = 10 \text{ mA}, I_O = \text{Open}$
Low Level Supply Current	$I_{CCL}$	—	0.9	3.0	mA	$V_{CC} = 5.5 \text{ V}, V_F = 0 \text{ V}, I_O = \text{Open}$
		—	1.2	3.0	mA	$V_{CC} = 20 \text{ V}, V_F = 0 \text{ V}, I_O = \text{Open}$
Threshold Input Current Low to High	$I_{FLH}$	—	2.3	5.5	mA	$C_g = 25 \text{ nF}, V_O > 5 \text{ V}$
Logic Low Short Circuit Output Current	$I_{OSL}$	25	185	—	mA	$V_O = V_{CC} = 5.5 \text{ V}, V_F = 0V$
		50	175	—	mA	$V_O = V_{CC} = 20 \text{ V}, V_F = 0V$
Logic High Short Circuit Output Current	$I_{OSH}$	—	-162	-25	mA	$V_{CC} = 5.5 \text{ V}, I_F = 6\text{mA}, V_O = \text{GND}$
		—	-185	-50	mA	$V_{CC} = 20 \text{ V}, I_F = 6\text{mA}, V_O = \text{GND}$
Input Forward Voltage	$V_F$	1.2	1.55	1.95	V	$I_F = 10 \text{ mA}$
Temperature Coefficient of Forward Voltage	$\Delta V_F / \Delta T$	—	-1.7	—	mV/°C	$I_F = 10 \text{ mA}$
Input Reverse Breakdown Voltage	$B_{VR}$	5	—	—	V	$I_R = 100 \mu\text{A}$
Input Capacitance	$C_{IN}$	—	70	—	pF	$f = 1 \text{ MHz}, V_F = 0V$

,

Propagation Delay Time to High Output Level	$t_{PLH}$	—	155	350	ns	With Peaking Capacitor
Propagation Delay Time to Low Output Level	$t_{PHL}$	—	145	350	ns	With Peaking Capacitor
Pulse Width Distortion	$ t_{PHL} - t_{PLH}  = P_{WD}$	—	6.2	250	ns	
Propagation Delay Difference Between Any Two Parts	$P_{DD}$	-100	—	250	ns	
Rise Time	$t_r$	—	18	—	ns	
Fall Time	$t_f$	—	15	—	ns	
Output High Level Common Mode Transient Immunity	$ CM_H $	20	—	—	kV/ $\mu\text{s}$	$ V_{CM}  = 1000 \text{ V}, I_F = 6.0 \text{ mA}, V_{CC} = 5 \text{ V}, T_A = 25^\circ\text{C}$
Output Low Level Common Mode Transient Immunity	$ CM_L $	20	—	—		$ V_{CM}  = 1000 \text{ V}, V_F = 0 \text{ V}, V_{CC} = 5 \text{ V}, T_A = 25^\circ\text{C}$



- "

480= Part Number .

U = Lead form option ,W or W1 .


Y = Tape and reel option (TA,TA1 or none) .

Z = 'V' code for VDE safety (This options is not necessary).

\* VDE Code can be selected.

S(TA)	Surface mount lead form (low profile) + TA tape & reel option	1000 units per reel
S(TA1)	Surface mount lead form (low profile) + TA1 tape & reel option	1000 units per reel

%"\$"




1. Manufacturer : ORIENT.
2. Part Number : 480.
3. Shape Code  : Lead form option ,W or W1 .
4. Year Code  '21' means '2021' and so on.
5. Week Code  01 means the first week, 02 means the second week and so on.
6. VDE Code . (Optional)
7. Anode.


\* VDE Mark can be selected.

%%"

(1).OR-480W




(2).OR-480W1




%&"

(1)OR-480W-TA




(2)OR-480W-TA1






(1)OR-480W1-TA



(2)OR-480W1-TA1



Type	symbol		
bandwidth	W	$16 \pm 0.3$ (0.63)	$16 \pm 0.3$ (0.63)
pitch	$P_0$	$4 \pm 0.1$ (0.16)	$4 \pm 0.1$ (0.16)
pitch	F	$7.5 \pm 0.1$ (0.3)	$7.5 \pm 0.1$ (0.3)
	$P_2$	$2 \pm 0.1$ (0.079)	$2 \pm 0.1$ (0.079)
interval	$P_1$	$16 \pm 0.1$ (0.63)	$12 \pm 0.1$ (0.47)

Encapsulation type	TA/TA1
amount pcs	1000



% " "

Packing type	Reel type
Tape Width	16mm
Qty per Reel	1,000pcs
Small box (inner) Dimension	345*345*58.5mm
Large box (Outer) Dimension	620x360x360mm
Max qty per small box	2,000pcs
Max qty per large box	20,000pcs

Material Code : 120PCXXXXXX  
 P/N : OR-XXXXXX  
 Lot No. : XXXXXX-XXXXX-TX-X  
 D/C : XXXX  
 Qty : XXXX PCS

内箱码

外箱码

"XXXXXXXXXXXXXXXX" (一体机序列码)

Made in China

1. Material Code :Product ID.
2. P/N :Contents with "Order Information" in the specification.
3. Lot No. :Product data.
4. D/C :Product weeks.
5. Quantity :Packaging quantity.



% ( "

(1).IR Reflow soldering (JEDEC-STD-020C compliant)


One time soldering reflow is recommended within the condition of temperature and time profile shown below. Do not solder more than three times.

Preheat

- Temperature Min (T Smin )
- Temperature Max (T Smax )

One time soldering is recommended within the condition of temperature.

Temperature	260+0/-5°C
Time	10 sec
Preheat temperature	5 to 140°C
Preheat time	30 to 80 sec



Allow single lead soldering in every single process. One time soldering is recommended.

Temperature	380+0/-5°C
Time	3 sec max

%) "








Figure 3. Typical Output Voltage vs. Forward Input Current

Figure 4. Typical Input Diode Forward Characteristic




Figure 5. Ci






Figure 8. Typical Propagation Delay vs. Supply Voltage




Figure 9.  $V_{OH}$  vs  $I_{OH}$  Across Temperatures




Figure 10.  $V_{OL}$  vs  $I_{OL}$  Across Temperatures

