



06H RoHS Compliant

贴片保险丝(抗浪涌型), CRLUS


SMD Fuse (High Inrush Current Withstand) 32V

Interrupting Rating:
50 Amperes at 32V DC

工作温度:
Operating Temperature:
-55°C ~ +125°C

材料:
Materials:
Substrate: ceramic/glass cover
Termination: silver over-plated with nickel and tin
Elements: silver

包装:
Packaging:
Automated taped, 5000PCS per reel,



额定电流的% % of Ampere Rating

熔断时间 Opening Time

目录编号: Catalog No. D:32V

目录编号 Catalog No.	额定电流 Ampere Rating	额定电压 Voltage Rating	标示 Marking	熔化热能 I ² T Melting Integral (A ² ·s)	认证 Approvals
					●表示已获认证 ●表示认证中 CRLUS
06H0250D	250mA	32V	D	0.00042	○
06H0375D	375mA	32V	E	0.00089	○
06H0500D	500mA	32V	F	0.0019	○
06H0750D	750mA	32V	G	0.0090	○
06H1100D	1A	32V	H	0.017	●
06H1150D	1.5A	32V	K	0.060	●
06H1200D	2A	32V	N	0.183	●
06H1250D	2.5A	32V	O	0.240	●
06H1300D	3A	32V	P	0.270	●
06H1400D	4A	32V	S	0.936	●
06H1500D	5A	32V	T	1.865	●
06H1600D	6A	32V	V	1.920	○
06H1700D	7A	32V	X	2.302	○
06H1800D	8A	32V	Z	3.015	○