



S H a W T c C.,Ld

MP28 S

SPECIFICATIONS

	C											
C	-55 +105 C											
	2 25											
D ^C	6.8 680 F											
C	20%() ; -35% +10%() ; -10% +20%() ; 0 +20%(A) 120 ; 120											
DC C	0.1C (A), C: (F), : () ()											
D F	B ()	2	2.5	4	6.3	7.5	10	12.5	16	20	25	()
()	D (.) F	0.06					0.08			20 C, 120		
E (100, 20 C)	; D : A/B											
C (100)	(+105 C) / (+20 C) 1.25 (-55 C) / (+20 C) 1.25											
F	A	2,000 105 ,										
	A											
	C C	20%										
	D F	150%										
	E C	150%										
	A	90% 95% 500 60 C (),										
	()	2	2.5	4	6.3	7.5	8	16	25			
	C	+70, -20%		+60, -20%		+50, -20%		+40, -20%				
	D.F. ()	200%										
	C											
	A	1,000 30 5 30 ,										
	A											
	C C	20%										
	D F	150%										
	E C	150%										

C	0.3()	0.2()	0.1()	1 0.2()	0.2()
7.3 4.3 2.8	7.3	4.3	2.8	2.4	1.3

MP28 S

C a ac c Tab

()	C (F)	()	E (A) (, 100) (.)	E (B) (, 100) (.)	(A) 100 (A)	(A) 100 B	(A .) 20 C
2	100	7.3*4.3*2.8	12	16	2200	2000	20
	150	7.3*4.3*2.8	6	9	3200	3000	30
	220	7.3*4.3*2.8	6	9	3400	3200	44
	270	7.3*4.3*2.8	6	9	3800	3500	54
	300	7.3*4.3*2.8	6	9	3850	3600	60
	330	7.3*4.3*2.8	4.5	8	4100	3800	66
	390	7.3*4.3*2.8	4.5	8	4250	3900	78
	470	7.3*4.3*2.8	4.5	8	4400	4000	94
	560	7.3*4.3*2.8	4.5	8	4800	4400	112
2.5	100	7.3*4.3*2.8	12	16	2200	2000	25
	150	7.3*4.3*2.8	6	9	3200	3000	38
	180	7.3*4.3*2.8	6	9	3300	3100	45
	220	7.3*4.3*2.8	6	9	3400	3200	55
	270	7.3*4.3*2.8	6	9	3800	3500	68
	330	7.3*4.3*2.8	4.5	8	4100	3800	83
	470	7.3*4.3*2.8	4.5	8	4400	4000	118
4	82	7.3*4.3*2.8	12	16	2250	2100	33
	150	7.3*4.3*2.8	12	16	2500	2300	60
	220	7.3*4.3*2.8	12	16	2950	2700	88
	330	7.3*4.3*2.8	12	16	3200	2900	132
6.3	22	7.3*4.3*2.8	35	45	1250	1150	14
	33	7.3*4.3*2.8	35	45	2000	1800	21
	47	7.3*4.3*2.8	25	40	2200	2000	30
	68	7.3*4.3*2.8	12	15	2400	2200	43
	100	7.3*4.3*2.8	12	15	2750	2500	63
	120	7.3*4.3*2.8	10	15	3200	2900	76
	150	7.3*4.3*2.8	9	15	3300	3000	95
	180	7.3*4.3*2.8	9	14	3600	3200	113
	220	7.3*4.3*2.8	9	14	3750	3300	139
270	7.3*4.3*2.8	7	12	4000	3600	170	
10	22	7.3*4.3*2.8	35	45	1700	1600	22
	27	7.3*4.3*2.8	18	30	1800	1700	27
	33	7.3*4.3*2.8	18	30	2000	1800	33
	39	7.3*4.3*2.8	18	30	2050	1850	39
	47	7.3*4.3*2.8	18	30	2200	1950	47
	68	7.3*4.3*2.8	18	30	2300	2050	68
	100	7.3*4.3*2.8	18	30	2750	2500	100
150	7.3*4.3*2.8	16	25	3100	2800	150	